

Directed vertical alignment liquid crystal display with fast switching

Mingxia Gu,^{a)} Ivan I. Smalyukh, and Oleg D. Lavrentovich

Chemical Physics Interdisciplinary Program, Liquid Crystal Institute, Kent State University, Kent, Ohio 44242

Received 28 October 2005; accepted 29 December 2005; published online 7 February 2006

We describe a directed vertical alignment (DVA) display mode based on a nematic liquid crystal (LC) doped with a chiral dopant and confined between two substrates, one of which is pretreated, say, by unidirectional rubbing or photoalignment. The design allows one to eliminate umbilical defects that appear during switching of the conventional VA cells and thus to obtain better contrast. Switching is 30% faster than for VA cells when optimized concentration of a chiral dopant is added and LC molecules at one of the substrates are slightly tilted from the cell normal due to the unidirectional surface treatment. © 2006 American Institute of Physics. DOI: [10.1063/1.2172299](https://doi.org/10.1063/1.2172299)

Liquid crystal displays (LCDs) have many advantages over other display technologies and are widely used nowadays. Various types of LCDs have been proposed, such as twisted nematic (TN), in-plane switching (IPS), and the patterned vertical alignment (PVA) mode, each with their advantages and disadvantages, see, for example, Ref. 1. The PVA mode is one of the best approaches in commercially available LCDs. In the OFF state, the molecules are normal to the two bounding plates thus the phase retardation of the cell is zero. An electric field applied to the bounding plates tilts the molecules and causes optical retardation; the material is of a negative dielectric anisotropy. Chevron-shaped patterned electrodes produce a fringe electric field with the in-plane component that directs the molecular tilt in the ON state. The resulting multifold symmetry of the director field gives an excellent viewing angle performance, high transmittance, and contrast ratio. Manufacturing does not require rubbing. However, the PVA mode is associated with the appearance and dynamics of defects of the director field in the ON state, which degrades the brightness and switching performance.

In this work, we first demonstrate that the defects are so-called umbilics,^{2,3} i.e., pairs of point defects at the bounding plates, by using the three-dimensional (3D) visualization technique of the fluorescence confocal polarizing microscopy (FCPM).⁴ We then propose a directed vertical alignment (DVA) mode that allows one to eliminate the umbilics. In the DVA cell, one of the substrates is treated (rubbing) to direct the molecular tilt in the azimuthal direction when the field is applied and thus to avoid the degeneracy of the director that causes the umbilics. In addition, the liquid crystal

The above VA mode as well as its patterned version, PVA, can be further improved by twisting the nematic matrix. As described previously,⁸⁻¹² a twisted structure increases contrast and brightness of the VA and PVA modes, but at the expense of a longer response time. For the DVA mode, we found experimentally that all the parameters, including the response time, Fig. 2 a , can be optimized by choosing the appropriate value s of d/p . There is an optimum value of d/p at which the response time is minimized, $d/p = 0.23$ in Fig. 2 a . We tested various DVA cells with different gaps while keeping $d/p = 0.23$, and compared their performance with the normal VA cells, Fig. 2 b . The total response time of the DVA is improved by more than 20% as compared to the normal VA. For both the DVA and the normal VA, the response time is proportional to d^2 , at least in the range of thicknesses $3-12 \mu\text{m}$ studied, as expected.⁹ We also performed measurements for a PDVA cell with $d/p = 0.23$ and a normal PVA cell. The response time behavior of the PDVA as a function of d/p is similar to that of the DVA cell. The rise, decay and total response time normalized by d^2 for the PVA mode are $\tau_{\text{rise}}/d^2 = 1.39 \text{ ms}/\mu\text{m}^2$, $\tau_{\text{decay}}/d^2 = 0.88 \text{ ms}/\mu\text{m}^2$, and $\tau_{\text{total}}/d^2 = 2.27 \text{ ms}/\mu\text{m}^2$, while for the PDVA cell with $d/p = 0.23$, they are generally smaller: $\tau_{\text{rise}}/d^2 = 0.87 \text{ ms}/\mu\text{m}^2$, $\tau_{\text{decay}}/d^2 = 0.87 \text{ ms}/\mu\text{m}^2$, and $\tau_{\text{total}}/d^2 = 1.74 \text{ ms}/\mu\text{m}^2$, respectively. The response time shown in Fig. 2 is measured using voltage pulses of a constant ampli-

The twisted structure also helps one to reduce the azimuthal angular dependence of the light transmission between crossed polarizers. The azimuthal angle φ is defined as the angle between the rubbing direction and the polarization of incoming light. The effect is illustrated in Fig. 3 where we compare the light transmission versus φ for the DVA cells with $d/p=0$ and $d/p = 0.23$. Besides the ratio d/p , one also needs to optimize the birefringence Δn of the LC and/or the corresponding thickness d . This optimization would depend on the voltage used to drive the cells. Our computer simulations based on Jones Matrix Method^{14,15} demonstrate that for a certain Δn , there is a well-defined cell gap d for which the azimuthal angular dependence of transmission, brightness, and contrast are optimized; the optimum value of Δnd is around $0.66 \mu\text{m}$ for $d/p = 0.23$.

To characterize the viewing angle, we attached crossed plastic polarizers to the outer sides of the glass plates. The polar and azimuthal angles that define the orientation of the cell normal with respect to the incident beam (achromatic light) are controlled with an accuracy better than 0.1° . Figure 4 shows the viewing angle performance of the PVA, DVA and PDVA cells measured under the same conditions; the data represent the contrast ratio for different polar and azimuthal angles. Note that the values of contrast ratio, especially off-axis, for all cells in Fig. 4 can be further increased by using high quality polarizers with better extinction coefficients and off-axis polarization quality. A multidomain PVA cell gives a much better viewing angle performance, Fig. 4 a, as compared to a mono-domain DVA cell, Fig. 4 b. However, viewing angle characteristics of the multidomain PDVA mode, Fig. 4 c, is comparable to those of the PVA, although at present still slightly worse than in the PVA. The cell parameters could be further optimized and the compensation films^{1,16} could be employed to further improve the viewing angle performances of both DVA and PDVA. Note that the rubbing direction in this work was chosen to be along one of the directions of the chevron electrodes, because in the ON state, the effect of the fringe field on the twisted director is maximized to improve the viewing angle. Other configurations are possible, too.

In conclusion, we have demonstrated the DVA mode, in which the appearance of defects-umbilics during the switching process is eliminated. As the result, the display shows

stable electro-optic characteristics, enhanced brightness and fast switching. The approach can be used as a nonpatterned DVA mode when the viewing angle is not important, or as